




PİSLİK TUTUCU

Y-STRAINER (FILTER)



ANMA ÖLÇÜSÜ NOMINAL SIZE	G (mm)	d (mm)	L (mm)	t (mm)
1/2"	15	14	53	11
3/4"	20	19	63	13
1"	25	24	74	13
1 1/4"	32	32	92	17
1 1/2"	40	39	98	16
2"	50	48	115	18
2 1/2"	65	60	139	18
3"	80	75	162	20

PARÇA ADI PART DESCRIPTION	MALZEME MATERIAL
Gövde Body	MS 58 Piring (CuZn39Pb2) MS 58 Brass (CuZn39Pb2)
Kapak Lid	MS 58 Piring (CuZn39Pb2) MS 58 Brass (CuZn39Pb2)
Filtre Filter	Paslanmaz Çelik Stainless Steel
O-ring O-ring	EPDM (Viton) EPDM (Viton)

- ISO 9001 Kalite Sistem Sertifikası. (ISO 9001 Quality System Management.) • ISO 228 Dışı X Dışı bağlantı. (ISO 228 Female by Female thread.)
- Endüstriyel, Tesisat ve sulama sistemlerinde kullanılmak üzere geniş kullanım alanı. (Can be used in a wide range of industrial, Plumping and agricultural applications.)
- Sıcaklık -10°C + 120°C. (Temperature -10°C + 120°C)